

# Rinse and Re-Pressure Pump Systems

SYSTEMS

EQUIPMENT

SUPPORT

VACUUMS

CONTROLS

SIGNAGE



## Sonny's Spot-Free Rinse System

These RO systems are designed to handle the rigors of the car wash environment. Each unit comes standard with a back-flushing carbon filter and 1in pipe. Includes 2HP, 125PSI @20GPM re-pressurization pump. Feed water pre-treatment is required. (208-240/480V AC, 60 Hz). Rain Bar and Mirror Solenoids included

Item No.	Description	RO Motor	Carbon Filter	Price
20006533	Spot Free, 1800 GPD 2HP	½HP	1½ CF back-flushing carbon	<b>\$8,184.00</b>
20006534	Spot Free, 4000 GPD 2HP	¾HP	1½ CF back-flushing carbon	<b>\$11,800.00</b>
20006535	Spot Free, 6000 GPD 2HP	1HP	2 CF back-flushing carbon	<b>\$13,540.00</b>
20006536	Spot Free, 8000 GPD 2HP	2HP	2 CF back-flushing carbon	<b>\$17,180.00</b>
20006515	Spot Free, 10000 GPD 2HP	3HP	2 CF back-flushing carbon	<b>\$21,550.00</b>
20006516	Spot Free, 16000 GPD 2HP	5HP	3 CF back-flushing carbon	<b>\$25,730.00</b>

## Sonny's Spot Free Re-Pressure Pump Systems

(Optional or replacement for other systems)

Several different options available to provide spot-free water at your wash. Low and medium pressure systems, depending on your preference. Both systems deliver 20-25GPM. Low pressure is at 30-50PSI and medium pressure is at 125-150PSI. The higher the pressure the more water you will use. The SRP153025 (#20003526) pump operates off of a bladder tank. Simply turn on a solenoid valve and the pump will deliver the water. The SRP212525 (#20003581) requires a signal from the car wash controller. Signal can be either 120 or 24V AC, please indicate when ordering.

Item No.	Description	Electrical	Flow Rate	Price
20003526	RO Re-Pressure System, 1-1/2HP 30-50PSI	240V AC 1-phase	20 - 25GPM Low Water Shut-Off	<b>\$4,500.00</b>
20003581	RO Re-Pressure System, 2HP 125-150PSI	208-240/480V AC 3-phase	20 - 25GPM Low Water Shut-Off	<b>\$4,500.00</b>