

# G2 Harshguard Doors

Designed to withstand the harshest car wash environments. The extruded PVC side seals ensure a tight seal along vertical edge with fiberglass windbars that won't bend, break, or kink. Slanted upper box aids water run-off. Automatic reset after impact or blow out. Reverse Safety Feature—Door automatically reverses if photo eye beam is broken. Stainless steel and aluminum components ensure durability against elements and chemicals.

## Features

- Welded seam construction
- Easily replaceable panels Water and dust proof direct quill drive to door
- Sealed oil bath right angle drive
- Manual crank override in case of power failure

## Specifications

<b>External Operator</b>	28in per second
<b>Cycle Per Hour</b>	24/40*/70†
<b>Motor</b>	110V
<b>Sizes</b>	Custom Sizes up to 16' x 16'
<b>Material</b>	18 oz vinyl & 40 mil clear PVC

\* With high duty cycle upgrade  
 † With high duty cycle and fan kit upgrade

Description	Price
Custom Quote	CALL

## Control Options



Welded Seams




Extruded PVC Side Seals




Extruded Aluminum Side Beams

## Mounting



### Face Mount

- Mount outside on the face of the building



### Projection Mount

- Mount inside the building beyond the existing security door
- Custom aluminum standoff brackets and corner gussets used to extend the door from the wall past the existing door
- Vinyl filler panels included to fill the space between the wall and door

## 18oz Vinyl Color Options

