WATER RECLAIM & ODOR CONTROL



SONNY'S Economatic Water Reclaim System

A new efficient Water Reclaim System that answers the call for an economically priced unit that filters particulate matter. Single, double, or triple hydro-cyclonic action. Automatic fresh water overrides in the event of low water or loss of prime. UL Listed control panel. Easy retrofit applications with a small footprint.

Standard Features

- · Hydro-cyclonic particle separators
- 120V AC powered control panel with hand /off / auto switch & on /alarm light
- · Patented Aqua Prep odor control technology
- TEFC, Self-primping pump

- 3-phase 208-230/460V AC 60 HZ
- . (2) Pump pressure gauges
- (1) Air flow meter
- Automatic fresh water override solenoid, with low water float switch & low flow alarm
- Dimensions: 48in W x 30in D x 66in H

Item #	Description	Price
10010629	Economatic Reclaim System, ERS100 100GPM	\$26875.00
10010630	Economatic Reclaim System, ERS150 150GPM	\$32180.00
10010632	Economatic Reclaim System, ERS50 50GPM	\$24300.00



SONNY'S SROC100 Stand-Alone Odor Control System

The SROC100 uses a proven and accepted way of producing ozone (0³), a powerful and proven oxidant. Air is pulled across the surface of a single Ultra Violet (UV) lamp. The Oxygen (0²) is converted to ozone (0³). This ozone stream is then injected into the dirty pit water stream. The highly reactive ozone is then discharged into the center pit of the car wash. No air dryer is required with this technology. A high concentration of ozone is not required when used efficiently.

Standard Features

- Can be added to any existing reclaim system
- Rids your car wash of the unpleasant odors typically associated with recycled water
- Stand-alone unit operates independent of your existing recycle wash reclaim system
- Operates on automatic and manual settings
- Pit water is pulled from the last collection (sediment) pit and discharges the pit water out into the center trench of the car wash, providing full flow that disinfects the recycled water
- · PLC controlled with display screen for system operation
- Pre-plumbed and pre-wired
- 1- UV Lamp, optic fiber lens for UV lamp inspection
- . 30GPM closed coupling pump with pre-filter
- 1HP 208-240/480V AC 3PH, 60Hz

CALL	Item #	Description	Price
· · · · · ·	20006494	SR0C100 Odor Control - Stand Alone	
WW	W-301	MVSDIFECTCOL	



SONNY'S SPOT FREE RINSE SYSTEM

Spot Free Affordable



SONNY'S Spot Free RO Systems

These RO systems are designed to handle the rigors of the car wash environment. Each unit comes standard with a back-flushing carbon filter, 3-phase electric (208-240/480V AC, 60 Hz), and 1 in pipe size. Includes 2HP, 125PSI @20GPM repressurization pump. Feed water pre-treatment is required.

Item #	Description	RO Motor	Carbon Filter	Price
20006533	Spot Free, 1800 GPD 2HP	½HP	1½ CF back-flushing carbon	\$8184.00
20006534	Spot Free, 4000 GPD 2HP	1HP	1½ CF back-flushing carbon	\$11800.00
20006535	Spot Free, 6000 GPD 2HP	1HP	2 CF back-flushing carbon	\$13540.00
20006536	Spot Free, 8000 GPD 2HP	2HP	2 CF back-flushing carbon	\$17180.00
20006515	Spot Free, 10000 GPD 2HP	ЗНР	2 CF back-flushing carbon	\$21550.00
20006516	Spot Free, 16000 GPD 2HP	5HP	3 CF back-flushing carbon	\$25730.00

SONNY'S Spot Free Re-Pressure Pump Systems (optional or replacement for other systems)

There are several different options available to provide spot-free water at your wash. We offer low and medium pressure systems, depending on your preference. Both systems deliver 20-25GPM. Low pressure is at 30-50PSI and medium pressure is at 125-150PSI. The higher the pressure the more water you will use. The SRP153025 (#20003526) pump operates off of a bladder tank. Simply turn on a solenoid valve and the pump will deliver the water. The SRP212525 (#20003581) requires a signal from the car wash controller. This signal can be either 120 or 24V AC, please indicate when ordering.

Item #	Description	Electrical	Flow Rate	Price
20003526	RO Re-Pressure System, 1-1/2HP 30-50PSI	240V AC 1-phase	20 - 25GPM Low Water Shut-Off	\$3900.00
20003581	RO Re-Pressure System, 2HP 125-150PSI	208-240/480V AC 3-phase	20 - 25GPM Low Water Shut-Off	\$4095.00

