

Compact Industrial Vacuum by AutoVac Industrial Vacuum Systems

Dustless Sanding System Starting at \$2195

Introducing EconoVac – a uniquely compact industrial vacuum. Its powerful motor is mounted on the filter separator, so EconoVac delivers outstanding suction but occupies a small space. The entire unit measures just 48" high and 30" in diameter.

EconoVac provides superior dustless sanding – a must for body shops and collision centers.

Features and Benefits

- EconoVac is ready to install, simply connect electrical and piping (magnetic starter included)
- Choose from a variety of engineered piping kits – ABS, zinc-coated steel, aluminum, etc.
- Compatible with overhead or underground piping
- Muffler included for quiet operation – 76 dB at 10'
- Lip seal gaskets provide positive leak-proof seal on doors
- Extremely durable 8-gallon polypropylene dirt container
- Lockable latches on filter bag area and dirt container
- Canister is constructed of durable 12 gauge steel with epoxy primer and urethane finish



As shown with optional 2-drop steel piping kit and stanchion just \$2890

A complete line of piping accessories and dustless sanding tools available



Compact Industrial Vacuum
by AutoVac Industrial Vacuum Systems

U.S. Patent Pending



Compact Industrial Vacuum
by AutoVac Industrial Vacuum Systems

Dustless Sanding System Starting at \$2195

Constructed of durable 12 gauge steel with fully welded seams and epoxy primer with urethane finish

Durable, efficient vacuum motors available in two sizes – 5hp and 7.5hp

Extremely durable 8-gallon polypropylene dirt container

Lockable latches

Multiple self-sealing polyester filter bags

Lip seal gaskets provide positive leak-proof seal

Motor is mounted directly to filter separator making a total footprint of just 30" in diameter

EconoVac measures just 48" tall by 30" in diameter, including motor

EconoVac Motor Specifications

- Custom engineered electric drive motor features 1-year warranty – available in two sizes
- Castings allow for fast heat dissipation, extending equipment life
- Impeller is dynamically balanced with the motor using electronic balancing analyzer
- Motor is mounted directly to filter separator making for compact design
- Intake and exhaust openings are directional controlled to accelerate airflow and improve suction

5hp Up to 2 simultaneous users		7.5hp Up to 4 simultaneous users	
Specifications			
48" tall		48" tall	
30" diameter		30" diameter	
385 pounds		425 pounds	
4" intake and exhaust openings		4" intake and 6" exhaust openings	
12 gauge steel		12 gauge steel	
Electrical Requirements			
Single Phase 60Hz	3 Phase 60Hz	3 Phase 60Hz	
208/230 volts AC	208/230/460 volts AC	208/230/460 volts AC	
Please consult your AutoVac professional for the following applications:			
Canada – 575 Volt customers		• For 50Hz	• High altitude above 3,000'

Upgrade to a Self-cleaning Pulse Jet Separator for an additional \$595.