



- | | | | |
|-----|--------------------------------------|---------|------------------------------------|
| MRS | DRIVE CONNECTION TERMINAL | — | ARROW SUPPLIED ENCLOSURE WIRING |
| 888 | DEVICE CONNECTION TERMINAL | — | CUSTOMER SUPPLIED ENCLOSURE WIRING |
| 888 | TERMINAL NOT FOR CUSTOMER CONNECTION | — | ARROW SUPPLIED FIELD WIRING |
| 888 | TERMINAL FOR CUSTOMER CONNECTION | — | CUSTOMER SUPPLIED FIELD WIRING |
| D | LOCATED ON ENCLOSURE DOOR | PLC-OUT | SUPPLIED PLC OUTPUT |
| I | LOCATED INSIDE ENCLOSURE | PLC-IN | SUPPLIED PLC INPUT |
| R | LOCATED REMOTE FROM ENCLOSURE | PLC-OUT | CUSTOMER PLC OUTPUT |
| C | LOCATED IN RESISTOR CAGE | PLC-IN | CUSTOMER PLC INPUT |

ENCLOSURE	TYPE	COOLING	BUS BAR RATING	HEIGHT	WIDTH	DEPTH
NEMA1	VENTED	NONE	36	24	8	
PART NUMBER						
1	23-NOV-09	***** AS BUILT *****				
0	03-NOV-09	ORIGINAL DRAWING ISSUE				
REV.	DATE	DESCRIPTION				

CUSTOMER NAME: _____ CUSTOMER DRAWING NUMBER: _____

AUTOVAC INDUSTRIAL VACUUM SYSTEMS
 TOLL FREE NUMBER - 1-888-628-8682
 EMAIL: SALES@AUTOVACINC.COM - WWW.AUTO-VAC.COM



PLANT: _____
 TITLE: 2x20HP 460VAC VFD PACKAGE
 SUBTITLE: WIRING DIAGRAM
 SCALE: NONE DRAWN: LHK
 DATE: 03-NOV-09 CHECKED: _____ B01129321 1