



- MRS DRIVE CONNECTION TERMINAL
- 888 DEVICE CONNECTION TERMINAL
- 888 TERMINAL NOT FOR CUSTOMER CONNECTION
- 888 TERMINAL FOR CUSTOMER CONNECTION
- D LOCATED ON ENCLOSURE DOOR
- I LOCATED INSIDE ENCLOSURE
- R LOCATED REMOTE FROM ENCLOSURE
- C LOCATED IN RESISTOR CAGE
- ARROW SUPPLIED ENCLOSURE WIRING
- - - CUSTOMER SUPPLIED ENCLOSURE WIRING
- ARROW SUPPLIED FIELD WIRING
- - - CUSTOMER SUPPLIED FIELD WIRING
- OUTPUT DESCRIPTION PLC-O01 SUPPLIED PLC OUTPUT
- INPUT DESCRIPTION PLC-I01 SUPPLIED PLC INPUT
- OUTPUT DESCRIPTION PLC-O02 CUSTOMER PLC OUTPUT
- INPUT DESCRIPTION PLC-I02 CUSTOMER PLC INPUT

ENCLOSURE	NEMA1	TYPE	VENTED	COOLING	NONE	BUS BAR RATING	30	HEIGHT	24	WIDTH	8	DEPTH
PART NUMBER												
0	21-NOV-11	ORIGINAL DRAWING ISSUE										
REV.	DATE	DESCRIPTION										

CUSTOMER NAME	CUSTOMER DRAWING NUMBER	PLANT	
	480-2006		
AUTOVAC INDUSTRIAL VACUUM SYSTEMS		TITLE 30HP 208-230VAC VFD PACKAGE	
TOLL FREE NUMBER - 1-888-628-8682		SUBTITLE WIRING DIAGRAM	
EMAIL: SALES@AUTOVACINC.COM - WWW.AUTO-VAC.COM		SCALE NONE DRAWN LHK	480-2006-01
		DATE 21-NOV-11 CHECKED	0