

## Flowline™ AR30 Belt Conveyor Retrofit

The FlowLine AR30 Belt Conveyor Retrofit is designed to fit any existing belt conveyor pit, including AVW®\*, whether it's a new build or replacement for a current operating unit. This conveyor includes all of the industry leading design features that make FlowLine conveyors best-in-class, including dual 30 inch belts and galvanized structure. Designed for easy installation to reduce down-time, your operation will be up and running in just days.

## **Features**

- Drop-in replacement conveyor featuring all of the FlowLine design advancements which has made it the industry standard.
- Bolt-together design has been modified to fit a narrower conveyor trench while using standard STI components for quick install and readily available replacement parts.
- Reduce maintenance with the FlowLine ExTrac System designed to eliminate dirt and contaminants to lengthen belt & sprocket life.

Specification	Sı	atior	ic	if	C	e	p	S
---------------	----	-------	----	----	---	---	---	---

оросинованоно	FlowLine™ SD Standard Duty	FlowLine™ HD HEAVY DUTY
Belt Type	Dual	Dual
Belt Thickness	3/4in	1in
Belt Car Pusher Row Spacing	18in	18in
Hinge Pin Material	Stainless Steel	Stainless Steel
Hinge Pin Diameter	1/4in	5/16in
Drive Type	Electric	Electric
Drive Configuration	Single Center	Single Center or Dual Side Mount
Wear Plate Material	Stainless Steel	Stainless Steel
Wear Plate Thickness	1/8in	3/16in
Fiberglass Grating Thickness	1.5in	1.5in
Fiberglass Grating Type	Open	Open
Rinsing System	FlowRinse™ 4-Stage	FlowRinse™ 4-Stage
Dirt Extraction	ExTrac™ System	ExTrac™ System



		STANDARD DUTY Conveyor	HEAVY DUTY Conveyor				
CONVEYOR		30in width	30in width				
Up to 150ft*	Conveyor Base	\$67,900.00	\$70,400.00				
	Per Foot	\$1,500.00	\$1,750.00				
*Call for pricing on conveyors over 150ft							



FlowLine™ AR-WB30-SD FlowLine™ AR-WB30-HD

## **TOTAL WASH DOWNTIME: 3 DAYS\***





















## AVERAGE 1600+ VEHICLES DAILY

Watch the video of this amazing conversion



\*Downtime estimate based on an actual case study with the availability of 200 man-hours of labor. All trademarks, logos, and brand names, including AVW®, used anywhere within this document are the property of their respective owners. All company, product, and service names used anywhere in this document are for identification purposes only.

